

## CAMERA SYSTEM

### Hathorn® H7

Hathorn® H7 systems come standard with a 7" (17.8 cm) daylight readable shatter resistant LCD monitor with 1,000 cd/m<sup>2</sup> of brightness, making it the brightest monitor in its class.

Available with Wi-Fi as an option, the H7 has an on-board hard drive with 64Gb (upgradable to 128Gb) capacity and USB recording allowing the user to record MPEG4 video and JPEG screen shots.

The H7 is a complete system with your choice of rugged Hathorn camera heads and three different stiffnesses of push rod. These systems are compatible with 18V Milwaukee® (or equivalent) batteries\* for ultimate portability and over 5 hours of runtime on a single charge.

Portability is never an issue with the H7 as these lightweight units are only 45 lbs. All H7s feature a footage counter, a 512Hz or 640Hz sonde and come equipped with 200 ft. (60 meters) of premium cable and your choice of camera head.

These rugged systems have a butt-welded steel frame construction and feature military-grade faceplates and connectors.



	Screen Shot Function		Daylight Readable Display		Internal Hard Drive- 64Gb or 128Gb		Self-Levelling Camera Heads
	Record to USB & HDD		512Hz or 640 Hz High Power Sonde		200 ft of Push Rod		Works with 18V Milwaukee® or Equivalent Batteries*
	Industry-Leading Warranty						

\* Battery: Milwaukee 18V is default, other brand 18V batteries can be used with adaptors.

FIND ALL HATHORN®  
MANUALS HERE



# HATHORN® H7

## CAMERA SYSTEM

## SPECIFICATIONS

### Display

Size & Display	7" (17.8 cm) impact-resistant, daylight-readable LCD
Resolution & Brightness	1024 × 600 pixels with 1,000 cd/m <sup>2</sup>

### Recording, Storage & Features

Recording Options	MPEG4 video (H.264 at 30 fps) & JPEG screenshot
Storage Options	USB, HDD or USB & HDD
USB Capacity	USB 2.0 up to 32 Gb
Hard Drive Capacity	64 Gb (standard) or 128 Gb (upgrade)
Menu Languages	English, Spanish, French
Footage Counter	Feet or meters - resettable
Sonde Frequencies	High power 512 Hz or 640 Hz
Push Rod	200 ft (60 m) of HDPE push rod with fiberglass core

### Power

Battery (not incl.)	Only Milwaukee® M18 18V or equivalent*
Battery Life	~5Hrs. using 3.0Ah
Battery Extender	Auto dimming & auto saving
AC/DC Adapter	12V - 4.1A (included)

Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Max Pipe Well Lit
H7-2143-SL	1.43"	✓	200 ft	1/2"	3"	10"
H7-2123-SL	1.23"	✓	200 ft	0.400"	2"	6"
H7-2100	1"	✓	200 ft	3/8"	1.5"	4"

### Weight & Dimensions

Weight without Battery	45 lb (20.4 kg)
Dimensions (L x W x H)	19" × 15.5" × 29.5" (48 cm × 39 cm × 75 cm)

### Environmental

Operating Temperature	14°F to 122°F (-10°C to 50°C)
Storage Temperature	-4°F to 140°F (-20°C to 60°C)



Hathorn® USA • 250 Lowery Court - Unit 2B Groveport, OH, 43125 USA  
Tel. +1-905-604-7040 • Email: [info@hathorncorp.com](mailto:info@hathorncorp.com), Sales Email: [sales@hathorncorp.com](mailto:sales@hathorncorp.com)  
[www.hathorncorp.com](http://www.hathorncorp.com)