

## CAMERA REELS

### Hathorn® Micron

Micron camera reels can be used with either Hathorn® control modules (H12+ recommended), or with your own mobile Apple/Android device, should you opt for the Wi-Fi option. The Wi-Fi option is a standalone camera system that allows live streaming and recording to up to three devices at the same time using Hathorn's free app. It is powered by an external Milwaukee® 18V or equivalent battery (sold separately), which can last over 12 hours.

Micron reels are trusted by plumbers, general contractors, and home inspectors to deliver crystal clear, recordable video inspections of small pipes 1.5" to 3". These reels offer a butt-welded steel frame construction and 100 ft of premium 1/4" push rod. Both styles of reel come equipped with 1" straight view camera heads fitted with super bright, cool running LEDs for optimal picture quality.

These features give Micron reels the ultimate in portability. The system comes with a full one-year warranty.

#### STANDARD REEL



#### WI-FI REEL



200 ft of Push Rod



512Hz or 640 Hz  
High Power Sonde



Works with 18V  
Milwaukee® or  
Equivalent Batteries\*



Industry-  
Leading  
Warranty

#### STANDARD VERSION

To be paired with  
Hathorn H12+  
Controller



#### WI-FI VERSION

To be paired with  
Phone or Tablet

\* Battery: Milwaukee 18V is default, other brand 18V batteries can be used with adaptors.

FIND ALL HATHORN®  
MANUALS HERE



# HATHORN® MICRON

## CAMERA REELS

## SPECIFICATIONS

### MICRON WI-FI SPECIFICATIONS

#### Display

Size & Display Dependent upon Apple/Android device

#### Recording, Storage & Features

Video Recording MPEG4

Screen Shot JPEG

File Storage Mobile device, cloud or USB

Footage Counter Feet or meters, resettable

Sonde Frequency 512 Hz or 640 Hz High Power Sonde

Push Rod HDPE - 100 ft. (30.4 m) of 1/4"

Start Up Time ~15 seconds


#### Power

Battery (not incl.) Only Milwaukee® M18 18V or equivalent\*

Battery Life 12 hrs. using 3.0Ah (sonde off)

AC/DC Adapter 12V - 4.1A (included)

Wi-Fi Frequency IEEE802.11b/g/n



 Download on the  
App Store

GET IT ON  
 Google play

Catalog #	Camera Head	Wi-Fi	Self Leveling	Rod Length	Rod Size	Max Pipe	Weight	Max Pipe	Dimensions
MC-1100	1"	✗	✗	100 ft	1/4"	3"	15 lbs.	12"	16" x 12" x 10"
MC-1078	7/8"	✗	✗	100 ft	1/4"	3"	15 lbs.	2"	16" x 12" x 10"
WMC-1100	1"	✓	✗	100 ft	1/4"	3"	16 lbs.	10"	16" x 12" x 10"
WMC-1078	7/8"	✓	✗	100 ft	1/4"	3"	16 lbs.	10"	16" x 12" x 10"

### STANDARD MICRON SPECIFICATIONS

#### Display

Size & Display Compatible with All Hathorn control modules

#### Features

Sonde Frequency High power 512Hz or 640Hz (available only with H12+ controller)

Push Rod HDPE - 100 ft. (30.4 m) of 1/4"

Recording, Storage & Power Please refer to H12+ specifications

#### Weight & Dimensions

Weight w/Battery 15lbs. (6.8 Kg) without battery

Dimensions (L×W×H) 16" x 12" x 10"

#### Environmental

Operating Temperature 14°F to 122°F (-10°C to 50°C)  
Storage

Temperature -4°F to 140°F (-20°C to 60°C)