

## CAMERA SYSTEM

### Hathorn® Wi-Fi Reels

Hathorn® Wi-Fi camera reels offer the convenience of streaming video inspections directly to two Apple or Android mobile devices at the same time using our free Hathorn app. Allows the user to take screen shots, record videos and make voice commentary. Save videos to your phone, email to your clients or attach to your route management software seamlessly.

All Hathorn cameras are portable and can be powered by external 18V Milwaukee® or equivalent batteries (not included) offering over 12 hours of run time on a single 3.0Ah battery. Batteries are inserted into the near indestructible Hathorn hub. No wires, no external battery cradles, just solid engineering. All Wi-Fi reels feature a footage counter and a 512Hz sonde.

Like all Hathorn products, they are genuinely made with a butt-welded steel frame construction and industry-leading HDPE premium cables.



	Screen Shot Function		Wi-Fi Reel for use with Phone or Tablet		Stream & Record to Mobile Device		Works with 18V Milwaukee® or Equivalent Batteries
	512hz or 640hz High Power Sonde		Stream & Record to Mobile Device		Self-Leveling Camera Heads		Industry-Leading Warranty
	200 to 400 ft of Push Rod						

\* Battery: Milwaukee 18V is default, other brand 18V batteries can be used with adaptors.

FIND ALL HATHORN®  
MANUALS HERE



# HATHORN® WI-FI REELS

## CAMERA SYSTEM

## SPECIFICATIONS

### Display

Size & Display      Dependent upon Apple/Android device

### Recording, Storage & Features

Video Recording      MPEG4

Screen Shot      JPEG

File Storage      Mobile device, cloud or USB

Footage Counter      Meters or feet - resettable

Sonde Frequency      512 Hz or 640 Hz High Power Sonde

Push Rod      HDPE - 100 ft. (30.4 m) of 1/4"

Start Up Time      ~15 seconds

### Power

Battery (not incl.)      Only Milwaukee® M18 18V or equivalent\*

Battery Life      ~ 12Hrs. using 3.0Ah

AC/DC Adapter      12V - 4.1A (included)

### Environmental

Operating Temperature      -14°F to 122°F (-10°C to 50°C)

Storage Temperature      -4°F to 140°F (-20°C to 60°C)

Wi-Fi Frequency      IEEE802.11b/g/n

### LARGE

Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
WLR-4143-SL	1.43"	✓	400 ft	1/2"	3"	45 lbs.	10"	33" x 29" x 16"
WLR-3143-SL	1.43"	✓	300 ft	1/2"	3"	55 lbs.	10"	33" x 29" x 16"
WLR-2143-SL	1.43"	✓	200 ft	1/2"	3"	45 lbs.	10"	33" x 29" x 16"

### MID

Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
WMR-2143-SL	1.43"	✓	200 ft	1/2"	3"	42 lbs.	10"	29" x 18" x 15"
WMR-2123-SL	1.23"	✓	200 ft	0.400"	3"	42 lbs.	6"	29" x 18" x 15"

### MINI

Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
WMN-2123-SL	1.23"	✓	200 ft	3/8"	2"	33 lbs.	6"	24" x 18" x 10"
WMN-2100	1	✗	200 ft	3/8"	1.5"	33 lbs.	4"	24" x 18" x 10"



 Download on the  
App Store

 GET IT ON  
Google play

 **hathorn**

Hathorn® USA • 250 Lowery Court - Unit 2B Groveport, OH, 43125 USA  
Tel. +1-905-604-7040 • Email: [info@hathorncorp.com](mailto:info@hathorncorp.com), Sales Email: [sales@hathorncorp.com](mailto:sales@hathorncorp.com)  
[www.hathorncorp.com](http://www.hathorncorp.com)



A Halma company